

## GPE CB Gaskets

**GPE CB Gaskets;** Plastic, elastic gaskets with minimal gas permeability!

**GPE CB Gaskets** are made of a special heat-resistant fibre material, with a unique impregnation, specially developed in-house.

This special, in-house developed, impregnation gives our range of **GPE CB Gaskets** its unique, water repellent, flexible sealing capabilities and minimises gas permeability.

**GPE CB Gaskets** are ready to use seals, which can be used at temperatures up to 800°C if used as an enclosed seal.

**GPE CB Gaskets** can be used, in a wide range of applications, particularly in the domestic appliances industry like stoves, domestic boilers, ovens etc.

**GPE CB Gaskets** are developed and manufactured in our in-house production facility in Steenberg, the Netherlands. They can be produced in all kinds of custom made, die-cutted parts.

Besides our standard GPE CB gaskets, we can also supply these gaskets with an additional service treatment.

### Physical properties

Colour	:	Red
Use Limit(*)	:	up to 800°C (as enclosed seal)
Melting Point	:	N.A.
Density	:	approx. 250-350 kg/m <sup>3</sup> (± 50 kg/m <sup>3</sup> )

\* Use limit refers to the maximum short term temperature limit. The maximum continuous use limit for GPE CB Gaskets depends on its application conditions.

